

```

/*****
/* Stata User File for HC10IF1 Data
/*
/* This file contains information and a sample Stata program to create a permanent
/* Stata dataset for users who want to use Stata in processing the MEPS data provided
/* in this PUF release.  Stata (StataCorp) has the capability to produce
/* appropriate standard errors for estimates from a survey with a complex sample
/* design such as the Medical Expenditure Panel Survey (MEPS).
/* The input file for creating a permanent Stata dataset is the ASCII data file
/* (HC10IF1.DAT) supplied in this PUF release, which in turn can be extracted from the
/* .EXE file. After entering the Stata interactive environment access the Stata DO-File
/* editor by clicking on the appropriate icon in the command line at the top of the
/* screen.  Copy and paste the following Stata commands into the editor and save as a
/* DO file.  A DO file is a Stata program which may then be executed using the DO command.
/* For example, if the DO file is named HC10IF1.DO and is located in the directory
/* C:\MEPS\PROG, then the file may be executed by typing the following command into
/* the Stata command line:
/*
/* do C:\MEPS\PROG\HC10IF1.DO
/* The program below will output the Stata dataset HC10IF1.DTA
*****/

#delimit ;
cd C:\MEPS\DATA;
log using HC10IF1.log, replace;
clear;

* INPUT ALL VARIABLES;
infix
    str    DUPERSID 1-8
    str    CONDIDX  9-20
    str    EVNTIDX  21-32
    str    CLNKIDX  33-56
    byte   EVENTYPE 57-57
using HC10IF1.dat;

*DEFINE VARIABLE LABELS;
label variable DUPERSID "PERSON ID: DUID+PID";
label variable CONDIDX  "CONDITION ID";
label variable EVNTIDX  "EVENT ID";
label variable CLNKIDX  "CLNK ID: CONDIDX+EVNTIDX";
label variable EVENTYPE "TYPE OF EVENT CONDITION IS LINKED TO";

*DEFINE VALUE LABELS FOR REPORTS;
label define HC10IF10001X
    1 "1 MVIS"
    2 "2 OPAT"
    3 "3 EROM"
    4 "4 STAZ"
    5 "5 DVIS"
    6 "6 OMED"
    7 "7 HVIS"
    8 "8 PMED" ;

* ASSOCIATE VARIABLES WITH VALUE LABEL DEFINITIONS;
label value EVENTYPE HC10IF10001X;

*DISPLAY A DESCRIPTION OF STATA FILE;
describe;

*LIST FIRST 20 OBSERVATIONS IN THE FILE;
list in 1/20;

save HC10IF1, replace;

#delimit cr

* data file is stored in HC10IF1.dta
* log  file is stored in HC10IF1.log

log close

/*****
NOTES:

1. This program has been tested on Stata Version 10 (for Windows).

2. This program will create a permanent Stata dataset.  All additional analyses
   can be run using this dataset.  In addition to the dataset, this program creates
   a log file named HC10IF1.LOG and a data file named HC10IF1.DTA.  If these files (HC10IF1.DTA and HC10IF1.LOG)
   already exist in the working directory, they will be replaced when this program is executed.

3. If the program ends prematurely, the log file will remain open.  Before running this
   program again, the user should enter the following Stata command: log close

4. The cd command assigns C:\MEPS\DATA as the working directory and location of the input
   ASCII and output .DTA and .LOG files and can be modified by the user as necessary.

5. Stata commands end with a carriage return by default. The command
   #delimit ;
   temporarily changes the command ending delimiter from a carriage return to a semicolon.

6. The infix command assumes that the input variables are numeric unless the variable name
   is prefaced by str.  For example, DUPERSID is the a string (or character) variable.

*****/
```