```
# Hitman Codes File for PC/Mac

# This file contains codes/cheats and a sample mod's program to create a mod/codes.
# Lines starting with a # are considered comments and are ignored by the parser.
# In the PDF manual, Codes/Cheats/Mod Tools are referred to as CHEATS.
# Codes/Cheats/Mod Tools are activated by the player in the game by typing the
# Codes/Cheats/Mod Tools are deactivated/disabled by typing the
# Codes/Cheats/Mod Tools are toggled on/off by typing the toggle command
# Codes/Cheats/Mod Tools are listed by typing the listcheats command
# Codes/Cheats/Mod Tools are listed by typing the listmods command
# Codes/Cheats/Mod Tools are listed by typing the listall command
# Codes/Cheats/Mod Tools are listed by typing the help command
# Codes/Cheats/Mod Tools are listed by typing the help <command_name>
```

```
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        995 "995 NO SPOUSE IN HOUSE"
        996 "996 MARITAL STATUS UNKNOWN"
        997 "997 LESS THAN 16 YRS OLD" ;

label define H530082X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 SPOUSE IN THE HOUSE"
        2 "2 NOT MARRIED/NO SPOUSE"
        3 "3 UNDER 16 INAPPLICABLE" ;

label define H530083X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 NO DIFFICULTY"
        2 "2 SOME DIFFICULTY"
        3 "3 A LOT OF DIFFICULTY"
        4 "4 UNABLE TO DO" ;

label define H530084X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 NO DIFFICULTY"
        2 "2 SOME DIFFICULTY"
        3 "3 A LOT OF DIFFICULTY"
        4 "4 COMPLETELY UNABLE TO DO IT"
        5 "5 COMPLETELY UNABLE TO WALK" ;

label define H530085X
        -1 "-1 INAPPLICABLE"
        1 "1 YES"
        2 "2 NO" ;

label define H530086X
        -1 "-1 INAPPLICABLE"
        1 "1 YES"
        2 "2 NO" ;

label define H530087X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 YES"
        2 "2 NO" ;

label define H530088X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 NO DIFFICULTY"
        2 "2 SOME DIFFICULTY"
        3 "3 A LOT OF DIFFICULTY"
        4 "4 UNABLE TO DO" ;

label define H530089X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 YES"
        2 "2 NO" ;

label define H530090X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 YES"
        2 "2 NO" ;

* ASSOCIATE VARIABLES WITH VALUE LABEL DEFINITIONS;
label value ACTDTY13 H530001X;
label value ACTLIM13 H530002X;
label value ADLHLP13 H530003X;
label value AGE13X H530004X;
label value AIDHLP13 H530005X;
label value BEGRFD13 H530006X;
label value BEGRFM13 H530007X;
label value BEGRFY13 H530008X;
label value BENDIF13 H530009X;
label value COGLIM13 H530010X;
label value DOBMM H530011X;
label value DOBYY H530012X;
label value EDUCYR H530013X;
label value EMPST13 H530014X;
label value ENDRFD13 H530015X;
label value ENDRFM13 H530016X;
label value ENDRFY13 H530017X;
label value FAMSIZ13 H530018X;
label value FNGRDF13 H530019X;
label value FTSTD13X H530020X;
label value HELD13X H530021X;
label value HIDEG H530022X;
label value HISPANX H530023X;
label value HISPCAT H530024X;
label value HOUR13 H530025X;
label value HPRIDK13 H530026X;
label value HPRIEU13 H530027X;
label value HPRING13 H530028X;
label value HPRIOG13 H530029X;
label value HPRIS13 H530030X;
label value HPRIV13 H530031X;
label value HRWAG13X H530032X;
label value HRWAY13 H530033X;
label value HSELIM13 H530034X;
label value IADLHP13 H530035X;
label value INSCOP13 H530036X;
label value INSRD13X H530037X;
label value KEYNESS H530038X;
label value LFTDIF13 H530039X;
label value MARRY13X H530040X;
label value MCAID13 H530041X;
label value MCAID13X H530042X;
label value MCARE13 H530043X;
label value MCARE13X H530044X;
label value MILDIF13 H530045X;
label value MNHLTH13 H530046X;
label value MNPROX13 H530047X;
label value MSA13 H530048X;
label value NUMEMP13 H530049X;
label value OFFER13X H530050X;
label value OTPUBA13 H530051X;
label value OTPUBB13 H530052X;
label value PANEL13 H530053X;
label value PRIDK13 H530054X;
label value PRIEU13 H530055X;
label value PRING13 H530056X;
label value PRIOG13 H530057X;
label value PRIOUT13 H530058X;
label value PRIS13 H530059X;
label value PRIV13 H530060X;
label value PROXY13 H530061X;
label value PSTAT13 H530062X;
label value PUB13X H530063X;
label value RACETHNX H530064X;
label value RACEX H530065X;
label value RCHDIF13 H530066X;
label value RDRESP13 H530067X;
label value REGION13 H530068X;
label value RFREL13X H530069X;
label value RTHLTH13 H530070X;
label value RTPROX13 H530071X;
label value RUCLAS13 H530072X;
label value RUENDD13 H530073X;
label value RUENDM13 H530074X;
label value RUENDY13 H530075X;
label value RUSIZE13 H530076X;
label value SCHLIM13 H530077X;
label value SELFCM13 H530078X;
label value SEX H530079X;
label value SOCLIM13 H530080X;
label value SPOUID13 H530081X;
label value SPOUIN13 H530082X;
label value STNDIF13 H530083X;
label value STPDIF13 H530084X;
label value STPRG13 H530085X;
label value TRINW13X H530086X;
label value UNABLE13 H530087X;
label value WLKDIF13 H530088X;
label value WLKLIM13 H530089X;
label value WRKLIM13 H530090X;

*DISPLAY A DESCRIPTION OF STATA FILE;
describe;

*LIST FIRST 20 OBSERVATIONS IN THE FILE;
list in 1/20;

save H53, replace;

#delimit cr

* data file is stored in H53.dta
* log  file is stored in H53.log

log close

/*****************************************************************************************
 NOTES:

 1. This program has been tested on Stata Version 10 (for Windows).

 2. This program will create a permanent Stata dataset.  All additional analyses
    can be run using this dataset.  In addition to the dataset, this program creates
    a log file named H53.LOG and a data file named H53.DTA.  If these files (H53.DTA and H53.LOG)
    already exist in the working directory, they will be replaced when this program is executed.

 3. If the program ends prematurely, the log file will remain open.  Before running this
    program again, the user should enter the following Stata command: log close

 4. The cd command assigns C:\MEPS\DATA as the working directory and location of the input
    ASCII and output .DTA and .LOG files and can be modified by the user as necessary.

 5. Stata commands end with a carriage return by default. The command
    #delimit ;
    temporarily changes the command ending delimiter from a carriage return to a semicolon.

 6. The infix command assumes that the input variables are numeric unless the variable name
    is prefaced by str.  For example, DUPERSID is the a string (or character) variable.

*****************************************************************************************/
```