```
;; Mixed Case File 0/0 Data                                                 ;;
;;                                                                          ;;
;; This file contains instances and a sample data program to create a      ;;
;; mixed case file. Instances are created using the CREATE-INSTANCE and    ;;
;; a data DEF message. Instance information has been separated by a number ;;
;; sign (#) followed by the instance name. Instances are created in the    ;;
;; order they are listed. Instances are created using the CREATE-INSTANCE  ;;
;; function and the Business Presentation Data Manager (BPDM).             ;;
;; Instances are created using the Business Information Manager (BIM) and  ;;
;; the BIM Data Manager (BDM). The BIM Data Manager is a subset of the BPDM ;;
;; and file. Other functions the Mixed Information Manager handles are the ;;
;; ability to create, delete, and modify instances, and to create, delete, ;;
;; and modify slots of a given instance. Instances are created in the BIM  ;;
;; Data Manager using the CREATE-INSTANCE function. Instances are created  ;;
;; in the BPDM using the CREATE-INSTANCE function. Instances are created   ;;
;; in CLIPS/BPDM. Keep file 0/0 Mix Dm executed in clips for following commands ;;
;;                                                                          ;;
;;                                                                          ;;
;; Mix presents Mixed Info: CREATE-INSTANCE, MODIFY-INSTANCE, DELETE-INSTANCE, ;;
;; SAVE-INSTANCE, RESTORE-INSTANCE, SAVE-INSTANCE-FILE, RESTORE-INSTANCE-FILE
```

```
        995 "995 NO SPOUSE IN HOUSE"
        996 "996 MARITAL STATUS UNKNOWN"
        997 "997 LESS THAN 16 YRS OLD" ;

label define H750083X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 SPOUSE IN THE HOUSE"
        2 "2 NOT MARRIED/NO SPOUSE"
        3 "3 UNDER 16 INAPPLICABLE" ;

label define H750084X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 NO DIFFICULTY"
        2 "2 SOME DIFFICULTY"
        3 "3 A LOT OF DIFFICULTY"
        4 "4 UNABLE TO DO" ;

label define H750085X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 NO DIFFICULTY"
        2 "2 SOME DIFFICULTY"
        3 "3 A LOT OF DIFFICULTY"
        4 "4 COMPLETELY UNABLE TO DO IT"
        5 "5 COMPLETELY UNABLE TO WALK" ;

label define H750086X
        -1 "-1 INAPPLICABLE"
        1 "1 YES"
        2 "2 NO" ;

label define H750087X
        -1 "-1 INAPPLICABLE"
        1 "1 YES"
        2 "2 NO" ;

label define H750088X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 YES"
        2 "2 NO" ;

label define H750089X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 NO DIFFICULTY"
        2 "2 SOME DIFFICULTY"
        3 "3 A LOT OF DIFFICULTY"
        4 "4 UNABLE TO DO" ;

label define H750090X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 YES"
        2 "2 NO" ;

label define H750091X
        -1 "-1 INAPPLICABLE"
        -7 "-7 REFUSED"
        -8 "-8 DK"
        -9 "-9 NOT ASCERTAINED"
        1 "1 YES"
        2 "2 NO" ;

* ASSOCIATE VARIABLES WITH VALUE LABEL DEFINITIONS;
label value ACTDTY13 H750001X;
label value ACTLIM13 H750002X;
label value ADLHLP13 H750003X;
label value AGE13X H750004X;
label value AIDHLP13 H750005X;
label value BEGRFD13 H750006X;
label value BEGRFM13 H750007X;
label value BEGRFY13 H750008X;
label value BENDIF13 H750009X;
label value COGLIM13 H750010X;
label value DOBMM H750011X;
label value DOBYY H750012X;
label value EDUCYR H750013X;
label value EMPST13 H750014X;
label value ENDRFD13 H750015X;
label value ENDRFM13 H750016X;
label value ENDRFY13 H750017X;
label value FAMSIZ13 H750018X;
label value FNGRDF13 H750019X;
label value FTSTD13X H750020X;
label value HELD13X H750021X;
label value HIDEG H750022X;
label value HISPANX H750023X;
label value HISPCAT H750024X;
label value HOUR13 H750025X;
label value HPRIDK13 H750026X;
label value HPRIEU13 H750027X;
label value HPRING13 H750028X;
label value HPRIOG13 H750029X;
label value HPRIS13 H750030X;
label value HPRIV13 H750031X;
label value HRWAG13X H750032X;
label value HRWAY13 H750033X;
label value HSELIM13 H750034X;
label value IADLHP13 H750035X;
label value INSCOP13 H750036X;
label value INSRD13X H750037X;
label value KEYNESS H750038X;
label value LFTDIF13 H750039X;
label value MARRY13X H750040X;
label value MCAID13 H750041X;
label value MCAID13X H750042X;
label value MCARE13 H750043X;
label value MCARE13X H750044X;
label value MILDIF13 H750045X;
label value MNHLTH13 H750046X;
label value MSA13 H750047X;
label value NUMEMP13 H750048X;
label value OFFER13X H750049X;
label value OTPUBA13 H750050X;
label value OTPUBB13 H750051X;
label value PANEL13 H750052X;
label value PRIDK13 H750053X;
label value PRIEU13 H750054X;
label value PRING13 H750055X;
label value PRIOG13 H750056X;
label value PRIOUT13 H750057X;
label value PRIS13 H750058X;
label value PRIV13 H750059X;
label value PROXY13 H750060X;
label value PSTAT13 H750061X;
label value PUB13X H750062X;
label value RACEAX H750063X;
label value RACEBX H750064X;
label value RACETHNX H750065X;
label value RACEWX H750066X;
label value RACEX H750067X;
label value RCHDIF13 H750068X;
label value RDRESP13 H750069X;
label value REGION13 H750070X;
label value RFREL13X H750071X;
label value RTHLTH13 H750072X;
label value RUCLAS13 H750073X;
label value RUENDD13 H750074X;
label value RUENDM13 H750075X;
label value RUENDY13 H750076X;
label value RUSIZE13 H750077X;
label value SCHLIM13 H750078X;
label value SELFCM13 H750079X;
label value SEX H750080X;
label value SOCLIM13 H750081X;
label value SPOUID13 H750082X;
label value SPOUIN13 H750083X;
label value STNDIF13 H750084X;
label value STPDIF13 H750085X;
label value STPRG13 H750086X;
label value TRINW13X H750087X;
label value UNABLE13 H750088X;
label value WLKDIF13 H750089X;
label value WLKLIM13 H750090X;
label value WRKLIM13 H750091X;

*DISPLAY A DESCRIPTION OF STATA FILE;
describe;

*LIST FIRST 20 OBSERVATIONS IN THE FILE;
list in 1/20;

save H75, replace;

#delimit cr

* data file is stored in H75.dta
* log  file is stored in H75.log

log close

/*****************************************************************************************
 NOTES:

 1. This program has been tested on Stata Version 10 (for Windows).

 2. This program will create a permanent Stata dataset.  All additional analyses
    can be run using this dataset.  In addition to the dataset, this program creates
    a log file named H75.LOG and a data file named H75.DTA.  If these files (H75.DTA and H75.LOG)
    already exist in the working directory, they will be replaced when this program is executed.

 3. If the program ends prematurely, the log file will remain open.  Before running this
    program again, the user should enter the following Stata command: log close

 4. The cd command assigns C:\MEPS\DATA as the working directory and location of the input
    ASCII and output .DTA and .LOG files and can be modified by the user as necessary.

 5. Stata commands end with a carriage return by default. The command
    #delimit ;
    temporarily changes the command ending delimiter from a carriage return to a semicolon.

 6. The infix command assumes that the input variables are numeric unless the variable name
    is prefaced by str.  For example, DUPERSID is the a string (or character) variable.

*****************************************************************************************/
```