```
;; Copyright (C) 2010-2013 Free
;;
;; This file contains instructions and a sample block program to convert a
;; Microsoft Windows Vista Ultimate Edition Service Pack 1 Version 6.0.6001
;; a.out PDP compiler. Since originally the .out binaries\n\n\n
```

```
label define H1250082X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         1 "1 YES"
         2 "2 NO" ;

label define H1250083X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         995 "995 NO SPOUSE IN HOUSE"
         996 "996 MARITAL STATUS UNKNOWN"
         997 "997 LESS THAN 16 YRS OLD" ;

label define H1250084X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         1 "1 SPOUSE IN THE HOUSE"
         2 "2 NOT MARRIED/NO SPOUSE"
         3 "3 UNDER 16 INAPPLICABLE" ;

label define H1250085X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         1 "1 NO DIFFICULTY"
         2 "2 SOME DIFFICULTY"
         3 "3 A LOT OF DIFFICULTY"
         4 "4 UNABLE TO DO" ;

label define H1250086X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         1 "1 NO DIFFICULTY"
         2 "2 SOME DIFFICULTY"
         3 "3 A LOT OF DIFFICULTY"
         4 "4 COMPLETELY UNABLE TO DO IT"
         5 "5 COMPLETELY UNABLE TO WALK" ;

label define H1250087X
         -1 "-1 INAPPLICABLE"
         1 "1 YES"
         2 "2 NO" ;

label define H1250088X
         -1 "-1 INAPPLICABLE"
         1 "1 YES"
         2 "2 NO" ;

label define H1250089X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         1 "1 YES"
         2 "2 NO" ;

label define H1250090X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         1 "1 NO DIFFICULTY"
         2 "2 SOME DIFFICULTY"
         3 "3 A LOT OF DIFFICULTY"
         4 "4 UNABLE TO DO" ;

label define H1250091X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         1 "1 YES"
         2 "2 NO" ;

label define H1250092X
         -1 "-1 INAPPLICABLE"
         -7 "-7 REFUSED"
         -8 "-8 DK"
         -9 "-9 NOT ASCERTAINED"
         1 "1 YES"
         2 "2 NO" ;

* ASSOCIATE VARIABLES WITH VALUE LABEL DEFINITIONS;
label value ACTDTY13 H1250001X;
label value ACTLIM13 H1250002X;
label value ADLHLP13 H1250003X;
label value AGE13X H1250004X;
label value AIDHLP13 H1250005X;
label value BEGRFD13 H1250006X;
label value BEGRFM13 H1250007X;
label value BEGRFY13 H1250008X;
label value BENDIF13 H1250009X;
label value COGLIM13 H1250010X;
label value DOBMM H1250011X;
label value DOBYY H1250012X;
label value EDUCYR H1250013X;
label value EMPST13 H1250014X;
label value ENDRFD13 H1250015X;
label value ENDRFM13 H1250016X;
label value ENDRFY13 H1250017X;
label value FAMSIZ13 H1250018X;
label value FNGRDF13 H1250019X;
label value FTSTD13X H1250020X;
label value HELD13X H1250021X;
label value HIDEG H1250022X;
label value HISPANX H1250023X;
label value HISPCAT H1250024X;
label value HONRDC13 H1250025X;
label value HOUR13 H1250026X;
label value HPRIDK13 H1250027X;
label value HPRIEU13 H1250028X;
label value HPRING13 H1250029X;
label value HPRIOG13 H1250030X;
label value HPRIS13 H1250031X;
label value HPRIV13 H1250032X;
label value HRWAG13X H1250033X;
label value HRWAY13 H1250034X;
label value HSELIM13 H1250035X;
label value IADLHP13 H1250036X;
label value INSCOP13 H1250037X;
label value INSRD13X H1250038X;
label value KEYNESS H1250039X;
label value LFTDIF13 H1250040X;
label value MARRY13X H1250041X;
label value MCAID13 H1250042X;
label value MCAID13X H1250043X;
label value MCARE13 H1250044X;
label value MCARE13X H1250045X;
label value MILDIF13 H1250046X;
label value MNHLTH13 H1250047X;
label value MSA13 H1250048X;
label value NUMEMP13 H1250049X;
label value OFFER13X H1250050X;
label value OTPUBA13 H1250051X;
label value OTPUBB13 H1250052X;
label value PANEL H1250053X;
label value PRIDK13 H1250054X;
label value PRIEU13 H1250055X;
label value PRING13 H1250056X;
label value PRIOG13 H1250057X;
label value PRIOUT13 H1250058X;
label value PRIS13 H1250059X;
label value PRIV13 H1250060X;
label value PROXY13 H1250061X;
label value PSTAT13 H1250062X;
label value PUB13X H1250063X;
label value RACEAX H1250064X;
label value RACEBX H1250065X;
label value RACETHNX H1250066X;
label value RACEWX H1250067X;
label value RACEX H1250068X;
label value RCHDIF13 H1250069X;
label value RDRESP13 H1250070X;
label value REGION13 H1250071X;
label value RFREL13X H1250072X;
label value RTHLTH13 H1250073X;
label value RUCLAS13 H1250074X;
label value RUENDD13 H1250075X;
label value RUENDM13 H1250076X;
label value RUENDY13 H1250077X;
label value RUSIZE13 H1250078X;
label value SCHLIM13 H1250079X;
label value SELFCM13 H1250080X;
label value SEX H1250081X;
label value SOCLIM13 H1250082X;
label value SPOUID13 H1250083X;
label value SPOUIN13 H1250084X;
label value STNDIF13 H1250085X;
label value STPDIF13 H1250086X;
label value STPRG13 H1250087X;
label value TRINW13X H1250088X;
label value UNABLE13 H1250089X;
label value WLKDIF13 H1250090X;
label value WLKLIM13 H1250091X;
label value WRKLIM13 H1250092X;

*DISPLAY A DESCRIPTION OF STATA FILE;
describe;

*LIST FIRST 20 OBSERVATIONS IN THE FILE;
list in 1/20;

save H125, replace;

#delimit cr

* data file is stored in H125.dta
* log  file is stored in H125.log

log close

/*****************************************************************************************
 NOTES:

 1. This program has been tested on Stata Version 10 (for Windows).

 2. This program will create a permanent Stata dataset.  All additional analyses
    can be run using this dataset.  In addition to the dataset, this program creates
    a log file named H125.LOG and a data file named H125.DTA.  If these files (H125.DTA and H125.LOG)
    already exist in the working directory, they will be replaced when this program is executed.

 3. If the program ends prematurely, the log file will remain open.  Before running this
    program again, the user should enter the following Stata command: log close

 4. The cd command assigns C:\MEPS\DATA as the working directory and location of the input
    ASCII and output .DTA and .LOG files and can be modified by the user as necessary.

 5. Stata commands end with a carriage return by default. The command
    #delimit ;
    temporarily changes the command ending delimiter from a carriage return to a semicolon.

 6. The infix command assumes that the input variables are numeric unless the variable name
    is prefaced by str.  For example, DUPERSID is the a string (or character) variable.

*****************************************************************************************/
```